

RAMCO Fisherman



MODEL CONSTRUCTION SPECS	RAMCO Fisherman
Length(LOA)mm	6000
Max Beam	2280
Approx. Weight (Hull Only, Incl. Std Options)	740
Capacity (Kg/Person)	540/6
Transom	XL Shaft 25"
Bottom Thickness	5mm
Side Thickness	4mm
Dead rise (Deg)	20
Recommended Max H.P.	115

STANDARD FEATURES

Full Curved Acrylic Wrap Around Screen	Spacious Dash for Instrument Layout
2 x Pedestal Seats with Arm Rests	Anchor Locker with Drain
Fully Welded Aluminium Tread plate Sole	Helm and Passenger Foot Rests
Attractive Aluminium Bow Rails	Aluminium Cabin Hatch
Aluminium Dash Handrail	Bow Sprit and Roller
Ample Easy Access Side Pocket Storage	Spacious Under Floor Storage
4 x Side Deck Rod Holders	'Surf Grip' Side Decks/Transom Top
Folding Alloy Dive Ladder	Transom – Angled with Outboard Bracket
Spacious Transom Storage	Convenient Transom Handrails
Non-Slip Boarding/Diving Platform	Sealed Under floor Buoyancy
Stylish <i>Ramco</i> Graphics	Cast Alloy Cross Bollard
Rubber Gunwale Strip Extrusion	Tubular Matting in Side Shelves
Trim-loc Rubber on Cabin and Shelving Edges	Switch Panel
Bilge System	Nav Lights
Steering	