

RAMCO FISHERMAN Hard Top



MODEL CONSTRUCTION SPECS	RAMCO FISHERMAN HT
--------------------------	--------------------

Length(LOA)mm	6100
Max Beam	2280
Approx. Weight (Hull Only, Incl. Std Options)	780
Capacity (Kg/Person)	540/6
Transom	XL Shaft
Hull Bottom Thickness	5mm
Side Thickness	4mm
Dead rise (Deg)	18.5
Recommended Max H.P.	130Hp

STANDARD FEATURES	
-------------------	--

<ul style="list-style-type: none"> Full Glass Screen and Side Windows 2 x Pedestal Seats with Arm Rests Fully Welded Aluminium Tread plate Sole Attractive Aluminium Bow Rails Aluminium Dash Handrail Ample Easy Access Side Pocket Storage 4 x Side Deck Rod Holders Folding Alloy Dive Ladder Transom Storage Alloy Tread Plate Boarding/Diving Platform Stylish <i>Ramco</i> Graphics Under Floor Fuel Tank (Incl. filler, sender) Trim-loc Rubber on Cabin and Shelving Edges Cockpit storage Switch Panel Bilge System 	<ul style="list-style-type: none"> Acrylic Cabin Port Light Windows Helm and Passenger Foot Rests Cule <i>Sleek Profile</i> Cabin Hatch Bow Sprit and Roller Aluminium Grab Handles in Hardtop Spacious Under Floor Storage 'Surf Grip' Side Decks/Transom Top Spacious Dash for Instrument Layout Transom – Angled with Outboard Bracket Convenient Transom Handrails Sealed Under floor Buoyancy Cast Alloy Cross Bollard Anchor Locker with Drain Tubular Rubber Matting in Side Shelves Nav Lights Steering
---	---

