

RAMCO Seahunter



MODEL CONSTRUCTION SPECS	RAMCO Seahunter
Length(LOA)mm	7450
Max Beam	2500
Approx. Weight (Hull Only, Incl. Std Options)	980
Capacity (Kg/Person)	720/8
Transom	XL Shaft 25"
Hull Bottom Thickness	5mm
Side Thickness	4mm
Dead rise (Deg)	20
Recommended H.P.	150-250

STANDARD FEATURES	
Full Curved Glass Screen & Sliding Side Windows	Acrylic Cabin Port Light Windows
2 x Pedestal Seats with Arm Rests	Helm and Passenger Foot Rests
Fully Welded Aluminium Tread plate Sole	Cule <i>Sleek Profile</i> Cabin Hatch
Attractive Aluminium Bow Rails	Bow Sprit and Roller
Aluminium Dash Handrail	Aluminium Grab Handles in Hardtop
Ample Easy Access Side Pocket Storage	Spacious Under Floor Storage
4 x Side Deck Rod Holders	'Surf Grip' Side Decks/Transom Top
Folding Alloy Dive Ladder	Spacious Dash for Instrument Layout
Transom Storage	Transom – Angled with Outboard Bracket
Alloy Tread Plate Boarding/Diving Platform	Convenient Transom Handrails
Stylish <i>Ramco</i> Graphics	Sealed Under floor Buoyancy
Under Floor Fuel Tank (Incl. filler, sender and gauge)	Cast Alloy Cross Bollard
Rubber Gunwale Strip Protector	Anchor Locker with Drain
Trim-loc Rubber on Cabin and Shelving Edges	Tubular Rubber Matting in Side Shelves
Switch Panel	Nav Lights
Bilge System	Steering